

# V10

## Wall Mounted Outdoor Residential LFP Battery



## Features



### Enhanced Safety

- Built-in Aerosol Fire Suppression System
- ESS Emergency Shutdown Feature
- Integrated DC Breaker & Pre-Charge Circuit



### High Power Output

- 5.88kW Continuous Output
- Whole Home Backup Capable



### Remote Monitoring and Upgrading



### Higher Energy Density

- Tier 1 Automotive Grade A 230Ah Cells
- Lighter Weight with Smaller Footprint



### Outdoor-Ready

- Weatherproof Enclosure with Integrated Heating Pad
- Wide Temperature Range for Cold Weather Applications



### Easy to Install

- Wall or Ground Mounted
- Effortless Installation and Quick Commissioning

# V 10 specifications



## Electrical

Nominal Voltage	51.2V
Nominal Capacity	230Ah
Nominal Energy	11.78kWh
Usable Energy	10kWh
Recommended Charge/Discharge Current	115A(5.88kW)
Peak Discharge Current	300A@15s

## General

Chemistry	LFP
Communication Interface	RS485 / CAN / WIFI / Dry Contact
Dimensions(L x W x H)	25.20 x 9.06 x 20.47inch / 640 x 230 x 520mm
Weight	220.5lbs / 100kg
Operating Temperature	Charge: 32~131°F / 0~55°C Discharge -4~131°F / -20~55°C
Cycle Life*	8000 Cycles
Altitude	<13123.35ft / 4000m
Warranty	12 Years
Ingress Protection	IP55
Mounting Method	Wall / Ground (W/ Optional Battery Tray)
Heating Pad (Integrated)	Temperature Rise: 14.4°F/h / 8°C/h

\*Test Conditions: 25°C, 0.5C/0.5C, 80% DoD

## Enhanced Safety Features

Hardware Level	Aerosol Fire Suppression DC Breaker & Pre-Charge Circuit
----------------	---

## Certifications

UL 9540 Ed.3 (2023), UL 9540A, UL 1973, CEC, SGIP

## Inverter Compatibility List

Main Inverter Partner



# Pytes

PYTES (USA) ENERGY, INC

Address: 13921 Senlac Dr, Farmers Branch, TX 75234  
Site: [www.pytesusa.com](http://www.pytesusa.com)  
Email: [pytesusa@pytesgroup.com](mailto:pytesusa@pytesgroup.com)

