

Pytes

V15



Features




Safe

LFP Chemistry, Tier 1 Automotive Cells & Field-Proven BMS



Smart

Remote Upgrading & Monitoring



Widely Compatible

Compatible with 20+ Inverters



Powerful

7.17kW Powerful Output,
14.34kWh High Capacity



Elegant

Sleek and Minimalist Design with Clean Lines, Featuring Hidden Interface



Easy To Install

Wheelable & Less Wiring
One Battery for the Whole Family

V15 Specifications



Electrical

Nominal Voltage	51.2V
Nominal Capacity	280Ah
Nominal Energy	14.34kWh
Recommended Charge/ Discharge Current	140A (7.17kW)
Maximum Charge/ Discharge Current	200A (10.24kW))
Peak Discharge Current	300A(15.36kW@15s)

General

Chemistry	LFP
Communication Protocol	RS485/CAN/Dry Contact/Wifi
Dimensions (W*D*H)	27.56*11.10*28.74inch/ 700*282*730mm
Weight	297.62 lbs/135KG
Operating Temperature	Charge: 32~131 F/0~55 C Discharge: -4~131 F/-20~55 C
Cycle Life	6000 cycles
Ingress Protection Code	IP21
Altitude	< 13123.35ft (4000m)
Warranty	10 Years

Inverters Compatibility List



Pytes

PYTES (USA) ENERGY, INC

Address: 13921 Senlac Dr, Farmers Branch, TX 75234
Site: www.pytesusa.com
Email: pytesusa@pytesgroup.com



LinkedIn



Facebook



YouTube



www.pytesusa.com
Pytes